

Technical Data

Issue 10 / November 2007

AT324 Double Sided Differential PVC Tape

General description



A black PVC film with the faced side coated with a permanent acrylic adhesive and the unfaced side coated with a removable acrylic adhesive. Interleaved with a white siliconised paper release liner.

- NEC (National Exhibition Centre) approved
- Clean peel
- Easy unwind
- Conformable to awkward shapes
- UV resistant

Technical Details

Typical values

Tape thickness (Excluding liner)	0.15mm
Release liner weight	80gsm
Release liner thickness	73 µm
Breaking Load	23 N/cm
Elongation	160%
Adhesion to Steel	
Faced Side	4.0 N/cm
Unfaced Side	2.0 N/cm
RoHS compliant	Yes
Service Temperature	-5°C to +60°C
Application Temperature	0°C to +40°C
Storage Temperature	+12°C to +25°C



NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

 **ADVANCE**
adhesive tapes



INVESTOR IN PEOPLE

Advance Tapes International Limited, PO Box 122,
Abbey Meadows, Leicester, LE4 5RA.

Tel: 0116 251 0191. Fax: 0116 265 2046. www.advancetapes.com

AFERA

Association des Fabricants Européens de
Rubans Auto-Adhésifs.