



TECHNICAL DATA

Scapa 1695

Metalised Polyester Adhesive Tape

DESCRIPTION

Scapa 1695 is a 23 μ coloured metalised polyester film coated with a long ageing acrylic adhesive system, with 45 μ total thickness and recommended for general splicing, decorative and sealing applications.

APPLICATIONS

- Decorative edging and reinforcing tape.
- Double glazed sealing.
- Repairing and splicing thermal blankets and screens in the horticultural industry.
- Splicing and web defects reflective tape for sensors.
- Suitable for a variety of long ageing and/or temperature resistant decorative, sealing and splicing applications.

PRODUCT BENEFITS

- Good shear resistance.
- High tensile strength.
- High chemical, moisture and solvent resistance.
- Long ageing adhesive.
- Wide continuous temperature resistance.
- Service temperature: -15°C to +130°C.

TECHNICAL PROPERTIES

	Unit	Nominal value	Test Method
Total Thickness	mm	0.045	AFERA 4006
Tensile Strength	N/cm	50	AFERA 4004
Elongation at Break	%	135	AFERA 4005
Adhesion to Steel	N/cm	2.6	AFERA 4001

STANDARD PRESENTATION

- Roll length:
 - a) 66 metres
 - b) 660 metres
- Roll width:
 - a) 12, 15, 19, 25, 30, 38 and 50 mm
 - b) 25, 38 and 50 mm
- Core: 76 mm Scapa branded cardboard core
- Packaging:
 - a) Bags (for 12 to 30 mm) - Concertina (for 38 and 50 mm)
 - b) Bulk in cartons
- Colour: Silver

RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Storage temperature between +10°C and +30°C. Under these conditions, the storage life of the tape in a temperate climate will be at least one year.

Surfaces should be clean, dry and free of dust, grease, oil or other contaminants.